


IP-COM Point-to-Multipoint Surveillance Wireless Transmission Solutions

Surveillance Wireless Transmission Solution For Orchard/Farm



Contents

01 Requirements

02 Solutions

03 Benefits


04 Recommendations

Orchard Scenario Requirements

#Orchard

Reservoirs

1. Prevention of vandalism
2. Prevention of water leakage



Fences

1. Prevention of fruit theft

Monitoring room

1. Monitoring people and vehicles

Junctions

1. Prevention of fruit theft
2. Recording the People Flow

Water tank

1. Prevention of vandalism
2. Prevention of water leakage

Entrance&Exit

1. Recording people and vehicles

Requirements Summary

- 1 Cameras need to be installed at orchard entrances&exits, road junctions, reservoirs and other areas. Stable signals need to be transmitted to the monitoring room



- 3 There is a height drop and obstruction between cameras and the monitoring room, which requires a central point in the middle for forwarding the signals.



- 2 Cameras and the monitoring room are far apart and scattered, ranging from 200m to 3km



- 4 The outdoor CPEs around the monitoring room can be powered by PoE switches or utility poles, others need to be powered by solar/wind power panels



Requirements Summary


5

Devices, installed in high outdoor locations, need to be protected from lightning, dust and water



7

Point-to-multipoint transmission need to be stable



6

Builders do not have enough network knowledge, have to simplify installation



Contents

01 Requirements

02 Solutions

03 Benefits

04 Recommendations

Solution-1-Mark Monitoring Points and backhaul planning

Mark all surveillance cameras locations, numbers and specifications, do on-the-spot investigation and plan data backhaul routes


#Orchard



Solution-2-Distance recording, Bandwidth counting and CPE model selecting


Record the distance of each backhaul line, calculate number of cameras, count bandwidth and select the appropriate models

#Orchard




Backhaul line	Distance	Camera quantity	Bandwidth	Connection method	AP Model	Station Mode
1#Fences->6#Reservoir	1.5km	2	8Mbps	P2P	CPE6S	CPE6S
6#Reservoir->5#Wired pole	1km	6	24Mbps	P2P	CPE6S	CPE6S
5#Wired pole->Monitoring room	800m	10	8Mbps	P2MP	BS9+ANT19-5G120	MS-5AC
1#Valley->1#Wired pole	500m	2	8Mbps	P2P	CPE6S	CPE6S
1#Wired pole->2#Wired pole	2.2km	5	20Mbps	P2P	CPE6S	CPE6S
2#Wired pole->Monitoring room	1.2km	7	28Mbps	P2MP	BS9+ANT19-5G120	MS-5AC
3#Wired pole->4#Wired pole	1.5km	3	12Mbps	P2P	CPE6S	CPE6S
1#Entrance&Exit->4#Wired pole	800m	2	8Mbps	P2P	CPE6S	CPE6S
4#Wired->Monitoring room	800m	8	32Mbps	P2P	MS-5AC	MS-5AC

Solution-3-How to ensure long distance data transmission




External signal amplifier

Enhances wirelessly transferable energy



Directional antenna

Focuses energy on a specific direction of emission and reception of electromagnetic waves, increasing effective signal utilization




ACK-Timeout Optimisation

Indoor APs or routers can only transmit up to 300 metres, while ACK-Timeout Optimisation extends limitation up to 25km


Solution-4-How to ensure the capacity can meet surveillance requirements

1 With 5Ghz 11AC technology to enhance wireless maximum speed up to 867Mbps




867Mbps
5GHz

2 Adopts wireless frequency bias anti-interference mechanism to reduce the interference from circumferential devices to the connection and improves the capacity



3 Provides more optional non-overlapping channels



Solution-5-How to power the devices


The devices support 12V/24V passive PoE, 12V1A DC power supply and standard PoE power supply and can draw power directly from the surrounding utility poles, solar panels or wind power integrated systems




Solution-6-How to align the devices

Outdoor CPEs usually have directional antennas, and angular misalignment will result in poor wireless signal quality. Installation can be done with the help of maps and reference points.

- 1 Drawing connection with AP site and station site
- 2 Look for landmarks near two points, install CPE in line with the landmarks.
- 3 Install client site with the landmark building. Adjust CPE according to signal LED or signal status on the web management.



#Orchard



Contents

01 Requirements

02 Solutions

03 Benefits

04 Recommendations

1. Stability is of Top Priority

As the surveillance video needs to be uploaded to the monitoring room 24 hours a day, stability of the CPEs' wireless connection is the most important guarantee in the application scenario of video surveillance wireless transmission.




Stability tests with cameras over 30 days
in a real environment




7*24 hours, -30°~+60° temperature
cycle aging test

2. Wireless performance optimisation technology for over 20% improvement in capacity

- 1 Channel redefinition to provide more optional non-overlapping channels




- 2 ipMAX point-to-multipoint user capacity optimisation




3. Simple installation and easy configuration


- 1 Plug and Play Kit**
The kits can be installed directly by factory default




- 2 Automatic pairing and bridging**
By default, two devices are automatically paired and bridged after powering on, instead of entering management page



- 3 P2MP auto-bridging**
Every single device supports automatic bridging. Once the two devices are automatically paired, others can join easily.



- 4 Bridging indicator**
Bridge LED can be used to recognize bridge status and signal strength



4. Three types of power supply available, low labor cost



1 Passive PoE

When the device is installed on the roof, it can be powered directly by the 12V/24V passive PoE Injector.



2 Standard PoE switch power supply


When the installation point is close to the monitoring room, device can share power by PoE switch



3 12V1A DC power supply

The device can be powered directly with 12V1A DC solar panels outdoors, no inverter conversion is required

5. A product portfolio solution



6. More useful tools

1 Wireless Data Capacity Test

Diagnose Speed Test Current Mode: Station

Diagnose Speed Test

↑ AVG RX	↓ AVG TX	↑ AVG Total
211.98 Mbps	243.13 Mbps	455.11 Mbps

☒ Client ☐ Server

IP Address of Peer AP Manual

IP Address 192.168.2.1

HTTP Port 80

User Name admin

Password admin


Test Group 10 (Range: 1 to 20)

Direction Bidirectional

Time 30 s (Range: 1 to 60)

Start

2 Frequency analysis for optimal channel selection



3 Automatic distance calculation between CPEs

LAN MAC Address		C8:3A:35:21:74:88	WLAN MAC Address		C8:3A:35:21:74:89
Wireless Status					
Working Mode	AP	AP's MAC Address		C8:3A:35:21:74:89	
SSID	BS9-AP	Signal Strength		<div><div></div></div> -52dBm	
Security Mode	WPA2-PSK	Background Noise		<div><div></div></div> -103dBm	
Channel/Radio Band	36/5180MHz	TX/RX Link		2X2	
Channel Bandwidth	80MHz	Transmit/Receive Speed		390Mbps/390Mbps	
TX Power	26dBm	IpMAX		Disabled	
Wireless Client	1	Distance		0.1km	
Statistics					
Throughput		Wireless Client	Interface	ARP Table	Routing Table
IP Address	MAC Address	Signal/Noise	Transmit/Receive	CCQ	Connection Duration
192.168.2.2	C8-3A:35:18:91:51	-52/-103dBm	390/390Mbps	100%	1 m55 s

Contents







01 Requirements

02 Solutions







03 Benefits

04 Recommendations

Product Recommendations - Cost-Effective Solutions

Scene	Device	Model	Image	Features	Layer
Monitoring room	Switch	G1124P-24-250W		<ul style="list-style-type: none"> ➤ 24*10/100/1000M RJ45 ports ➤ All 24 ports support af/at PoE power supply ➤ Whole device PoE Power Supply: 250W 	Access layer
Monitoring room	Basestation	BS9		<ul style="list-style-type: none"> ➤ 2*RG-SMA RF ports ➤ 5GHz 11AC 867Mbps ➤ 1*Gigabit Ethernet port ➤ TDMA supported, point-to-multipoint with up to 20 cameras 	Access layer
Monitoring room	Antenna	ANT19-5G120		<ul style="list-style-type: none"> ➤ 120° horizontal wireless transmission ➤ 5GHz frequency ➤ 19dBi high-gain antenna ➤ Range up to 5km connecting to BS9 	Access layer
Monitoring room	Outdoor CPE	MS-Loco5AC		<ul style="list-style-type: none"> ➤ Transmission range 5km ➤ 5GHz 11AC 867Mbps ➤ 2*Gigabit Ethernet port ➤ Standard PoE/24V0.5A/12V1A DC ➤ 2km point to point with 20 cameras 	Access layer
Transmit point	Outdoor CPE	MS-Loco5AC			
Transmit point	Switch	G1005		<ul style="list-style-type: none"> ➤ 5 *10/100/1000Mbps ports ➤ All ports 6KV lightning protection 	Access layer
Valley	Outdoor CPE	CPE6S		<ul style="list-style-type: none"> ➤ Transmission range 5km ➤ 5GHz 11AC 867Mbps ➤ 4*FE ports ➤ 12V1A DC/Passive PoE ➤ 2km point to point with 8 cameras 	Access layer
Fences/Entrance&Exit	Outdoor CPE	CPE6S			

Product Recommendations - High-Performance Solutions

Scene	Device	Model	Image	Features	Layer
Monitoring room	Switch	G1124P-24-250W		<ul style="list-style-type: none"> ➤ 24*10/100/1000M RJ45 ports ➤ All 24 ports support af/at PoE power supply ➤ Whole device PoE Power Supply: 250W 	Access layer
Monitoring room	Basestation	BS9		<ul style="list-style-type: none"> ➤ 2*RG-SMA RF ports ➤ 5GHz 11AC 867Mbps ➤ 1*Gigabit Ethernet port ➤ TDMA supported, point-to-multipoint with up to 20 cameras 	Access layer
Monitoring room	Antenna	ANT19-5G120		<ul style="list-style-type: none"> ➤ 120° horizontal wireless transmission ➤ 5GHz frequency ➤ 19dBi high-gain antenna ➤ Range up to 5km connecting to BS9 	Access layer
Monitoring room	Outdoor CPE	MS-5AC		<ul style="list-style-type: none"> ➤ Transmission range 10km ➤ 5GHz 11AC 867Mbps ➤ 1*Gigabit Ethernet ports ➤ Standard PoE/24V0.5A/12V1A DC ➤ 2km point to point with 40 cameras 	Access layer
Transmit point	Outdoor CPE	MS-5AC			
Transmit point	Switch	G1005		<ul style="list-style-type: none"> ➤ 5 *10/100/1000Mbps ports ➤ All ports 6KV lightning protection 	Access layer
Valley	Outdoor CPE	MS-Loco5AC		<ul style="list-style-type: none"> ➤ Transmission range 5km ➤ 5GHz 11AC 867Mbps ➤ 2*Gigabit Ethernet ports ➤ Standard PoE/12V1A DC/Passive PoE ➤ 2km point to point with 20 cameras 	Access layer
Fences/Entrance&Exit	Outdoor CPE	MS-Loco5AC			

IP-COM / THANKS

WORLD WIDE WIRELESS